

# EMERGENCY LIGHTING AND ORIENTATION SYSTEMS

ARSEL 



## BETALITE EMERGENCY LIGHTING FIXTURE

- Surface mounting, ABS plastic case
- Economic exit marking
- Transparent acrylic light panel

- It is designed for economic markings that can be used in the wall and door applications.
- There are 2 fluorescent lamps with fluorescent lamps and continuous lighting. One of the lamps is on line voltage and the other is power failure.
- In standard condition, IP60 is included in the protection class
- All plastic equipments provide necessary flame-proof conditions
- The mains supply voltage is standard 220 volts AC 50 Hz.
- Charging time for first use is 24 hours.
- It can withstand fluctuations up to 285 volts at mains voltage.
- Switches to emergency lighting mode under 150 volts, charging over 185 volts
- It is manufactured according to TS 8710 EN60598-2-22 standard in the framework of ISO 9001-2000 quality management system.

### USAGE AREAS

- Fire ladders
- Control center management rooms
- Boiler rooms
- Offices
- Grocery stores
- Corridors
- Restaurants and bars
- Universities, Student dormitories, Schools and colleges

### LAMP OPTIONS

- G5 socket T5 8w fluorescent bulb, 6500°K
- White light LED bulb, 6500°K

### BODY STRUCTURE

- Body - ABS plastic case
- Label panel - transparent acrylic panel white latex foil via printing application
- Nickel-cadmium in all models

### OPTIONS

- Continuous and emergency models
- 1-2-3 hour emergency backup times



## BETALITE EMERGENCY LIGHTING FIXTURE

MODEL CODE	LIGHTING STYLE	MOUNTING STYLE	LAMP	LIGHT FACE	DURATION (minute)	DIMENSIONS (W-L-H)mm	WEIGHT	IP CLASS	ISOLATION CLASS	OPERATION TEMP	POWER CONSUMPTION	OPERATING VOLTAGE
AEB-03111	Emergency Light	Wall Mount	8 wat	Single Side	Emergency 60 m.	74x355x118mm	0,760kg	60	I	-16/+45°	3w	220-240
AEB-03112	Emergency Light	Wall Mount	8 wat	Single Side	Emergency 120 m.	74x355x118mm	0,760kg	60	I	-16/+45°	3w	220-240
AEB-03113	Emergency Light	Wall Mount	8 wat	Single Side	Emergency 180 m.	74x355x118mm	1,00kg	60	I	-16/+45°	3w	220-240
AEB-03113-L	Emergency Light	Wall Mount	20xF LED	Single Side	Emergency 180 m.	74x355x118mm	0,760kg	60	I	-16/+45°	1w	220-240
AEB-03211	Combined m.	Wall Mount	2x8 wat	Single Side	Emergency 60 m.	74x355x118mm	1,10kg	60	I	-16/+45°	11w	220-240
AEB-03212	Combined m.	Wall Mount	2x8 wat	Single Side	Emergency 120 m.	74x355x118mm	1,10kg	60	I	-16/+45°	11w	220-240
AEB-03213	Combined m.	Wall Mount	2x8 wat	Single Side	Emergency 180 m.	74x355x118mm	1,40kg	60	I	-16/+45°	11w	220-240
AEB-03213-L	Maintained	Wall Mount	20xF LED	Single Side	Emergency 180 m.	74x355x118mm	0,770kg	60	I	-16/+45°	2w	220-240
AEB-03010-L	Mains Light	Wall Mount	20xF LED	Single Side	-	74x355x118mm	0,710kg	60	I	-16/+45°	1w	220-240

## DIMENSIONS

